

Historic, Archive Document

Do not assume content reflects current scientific knowledge, policies, or practices.

Report No. NTML-WRG-553

Report Date 25 April 1977

TRANSLATION
NAL ~~XXXXXXXXXX~~ No. _____

Author(s): ²⁵⁰¹ Rozhkov, N. P.; Baukov, A. V.

TRANSL
22963

EXTRA COPY
Title: ²⁵⁰¹ THE PROBLEM OF DETERMINING THE DEFORMATION PROPERTIES OF SOIL
²⁰²¹ ~~В~~ вопросы определения деформативных свойств почв

Translated from: Scientific Reports of the Ukrainian Agricultural Academy, 1973, Issue 100, pp. 100-115.

⁴¹⁰¹ [Nauchnye Trudy USKhA (Ukrainian S-Kh. Akademiya), Vyp. 100, s. 100-115, 1973.]

Translated by: Dr. William R. Gill, Soil Scientist, USDA, ARS, SR, National Tillage Machinery Laboratory, P. O. Box 792, Auburn, Alabama 36830

Abstract: A study was made of the deformation of the soil by a roller. The deformation properties of the soil were decreased significantly both by increase in soil bulk density and speed of movement of the roller. The modulus of deformation conversely increased with these same values.

Keywords: Rollers, deformation, bulk density, soil compaction, translations, USSR

Available from: U.S. Department of Agriculture
National Agricultural Library
Division of Lending
Beltsville, Maryland 20705

OR

Translations Department
The John Crerar Library
35 West 33rd Street
Chicago, Illinois 60616

(When ordering refer to NAL ~~XXXXXXXXXX~~ No. above as well as author and title.)

TRANSLATION

(a)

1000

1000

1000

1000

1000

1000

1000

1000

1000

1000

1000

THE PROBLEM OF DETERMINING THE DEFORMATION PROPERTIES OF SOIL

[K voprosy opredeleniya deformatiznykh
svoistv pochv]

N. P. Rozhkov, A. V. Baukov

(Scientific Reports of the Ukranian Agricultural
Academy, 1973, Issue 100, pp. 100-115.)
[Nauchnye Trudy USKhA (Ukrainian S-Kh. Akademiya)
Vyp. 100, s. 100-115, 1973.]

As is known, the soil is a complex elastic-viscous-plastic media [7] possessing a whole series of properties, the study of which are very difficult. Therefore, for improving the physical nature of the phenomenon occurring during the interaction of working tools of agricultural machines with the soil, we are ordinarily limited by a small number of indices of its condition.

The process of deformation of soils, as has been shown by studies of V. G. Berezantsev [2], A. S. Kushnarev [10], and other authors, consists of two phases: 1. (phase of compression/local shear); 2. phase of significant shear.

In the first phase a converging together of the particles occurs, and their density increases because of an isotropic compression. The force of the pressure during this does not exceed the limit of strength of the soil.

With a further increase of pressure a second phase starts - the plastic flow of the soil along the surface of the limiting resultant (surfaces of significant shear). The limit of load in this phase depends on the coefficient of internal friction and cohesion of the soil.

In the first phase between compacting pressures and relative deformation of compaction (elastic and residual) there exists a linear relation [1,3], characterized by the modules of deformation E_0 . The magnitude of it depends on the type of soil, its moisture density and method of loading [4,5,6,8].

The large interval of the values of the modulus of deformation [4,6,8] causes the necessity of determining its magnitude for each type and condition of soil with a definite speed of loading, which must equal the speed of movement of the soil working tools.

The deformation corresponding to the first phase is made more sharply with an interaction of a smooth roller with the soil. During this it is suitably accurate to consider the speed of loading.

We will examine the scheme of interaction of the roller with the soil (Fig. 1), the pressure of which does not exceed its limit of flow.

1000
1000
1000

As is known, the
assessing of the
cult. The
correcting of
which the
its condition

The process
V. G. B...
of the
efficiency

In the
their
of the
soil.

With a
flow of
of eight
coefficient

In the
tion of
tion [1,
tude of
of loading

The large
causes the
dition of
speed of

The delay
with an
entirely

We will examine the
(Fig. 1), the

We suggest that the resulting normal reaction of the soil N is axially symmetrical for the area of contact $-a < x < a$. The hemispherical area of contact is determined from the condition, that the pressure on the operating surface $P(x)$ must be limiting everywhere, including the edge of this area [9], i.e.

$$P = A a^2, \quad (1)$$

where $A = \frac{1}{2\nu} [f_1''(0) + f_2''(0)]$ = the coefficient, depending on the shape of the compressed body and the deformation properties of the soil, which is determined by the expression:

$$\nu = \frac{2}{\pi E_0} (1 + M^2), \quad (2)$$

where M = the coefficient of lateral expansion of the soil.

Substituting the value of A in equation [1] according to the compressing force we will determine the hemisphere area of contact $-a$:

$$a = \sqrt{2PR\nu}, \quad (3)$$

Where R = the radius of the roller.

From Fig. 1 it is clear, that the ratio of the depth of rut h to the width of area of contact $2a$ is equal to the ratio of force of resistance to rolling of the roller P_c to the compressing force P .

[Translator's Note: equation missing in the original.] (4)

Substituting the values of a and P in expression (4) we get the equation determining the value of parameter ν characterizing the deformation properties of the soil in the form:

$$\nu = \frac{Bh^2}{4P_c^2 R} \sqrt{G^2 + P_c^2}, \quad (5)$$

We have
received
from
the
area

where

where
force

where
of
the

where
the

where B = the width of the roller;
 G = the weight of the roller.

As is clear from the secured equation, determination of the deformation properties of the soil in the form of a general parameter by experimental means does not cause great difficulty. For this it is sufficient to measure the depth of the rut and the draft resistance of the roller with a consideration of the speed of its movement and the condition of the soil. Knowing the magnitude of the general indicator of deformation properties and the coefficient of lateral expansion of the soil by equation [2], it is possible to easily determine the magnitude of its modules of deformation. Therefore, the parameter v we take in the capacity of a basic index of the condition of the soil in the time of the first phase-compaction.

The experimental equipment for determining this parameter consists of a trolley, on which were mounted the measuring apparatus (8ANCH-7m amplifier, N-105 oscillograph, power supply P-131) and the roller width $B = 0.8$ m, diameter $D = 0.6$ m and weight $G = 280$ kg.

The study was conducted on a heavy-loam southern black soil, the moisture of which was maintained in the range of 18-20%. The load on the roller remained constant.

The speed of movement was varied in the range from 0.3 to 1.2 m/sec with intervals of 0.3 m/sec, and the volume weight of the soil varied from 0.4 to 1.4 g/cm³.

Each speed of movement of the roller and density of soil corresponded to 5 replications of the tests. The draft resistance of the roller measured with the help of a dynamometer link, mounted between the roller and the trolley, was recorded on the oscillograph chart and worked up by the planimeter method.

The depth of the rut was measured with an accuracy up to 0.5 mm.

The test data were worked up by the methods of mathematical statistics with the help of a "MROMIN-M" computer according to a standard program.

Results of the experimental study are presented in Fig. 2.

Since the coefficient M for soil varies in the range from 0.06 to 0.3 (8), then according to expression (2) in the range of error of the tests (9%) it is possible to determine the value of the modulus of deformation even with a maximum value of $M = 0.3$. With lesser values of M the accuracy of the calculations increases up to 0.5% (when M equals 0.06). The law of creation of the modulus of deformation E_0 in relation to the density of the soil and speed of movement of the roller is presented in figure 3.

The value of E_0 , secured as a result of the study, is found in the range from 5 to $1.0 \cdot 10^3$ kg/cm², which is confirmed by experimental studies of Kh. A. Rakhmatulina [6], A. S. Kushnareva [9], S. R. Meschyana [4,5], and other authors.

As the

proper

means

one is

advised

that

is

tion.

of the

The

trial

2-12

diagram

The

of which

terminal

The

inter

in 1.5

each

3

with

trial

inter

The

The

with

Results

Since

then

it is

with

the

creation

the

The

from 2

to 1.5

to 1.5

other

We suggested a method of determining the deformation properties of the soil considering the speed of loading and its condition and it can find use when establishing parameters of soil working implements.

LITERATURE

1. Alekseev, N. A. Method of determining the dynamic characteristics of soil with large pressures. Symposium "Soil Dynamics", No. 44, Moscow, Gosstroitel', 1951.
2. Berezantsev, V. G. Assymetric problem of the theory of limiting results of granular media. Moscow, Stroizdat, 1954.
3. Lukanin, Yu. V. The linear deformation of soils. Scientific paper of the Faculty of Mechanization of Penzensk Agricultural Institute, Vyp. 8, Penza., 1967.
4. Meschyan, S. R. The influence of speed on the deformation properties of viscous soils. Izvestiya Acad. Sci. USSR, Vol. 12, No. 4, 1959.
5. Meschyan, S. R. Creep of clay soils. "Science", Erevan, 1967.
6. Rakhmatulin, Kh. A., et al. Problems of the dynamics of soils. M. G. U. Publishing House, 1964.
7. Kushnarev, A. S. Rheological model of the soil during the interaction on it of soil working implements. Problems of Mechanization of Agriculture. Vol. 17, Reports, Mimskh., 1971.
8. Kushnarev, A. S., Kuz'min, V. L. The problem of determining the instantaneous modulus of elasticity of soil. Report of the first scientific-technical conference on the problem, "The complexity of mechanization of bringing stony soils into production." Erevan, 1965.
9. Kushnarev, A. S., Baukov, A. V., Rozhkov, P. N. Use of methods of the theory of contact deformations during determining the pressure on the soil by the roller and nonpowered wheels of tractors and agricultural machines. Mimskh. Problems of the Mechanization of Agriculture. Issue 2. Melitolol, 1967.
10. Kushnarev, A. S. Utilization of the rheology of soils for determining the optimum parameter of working tools of soil working machines. Scientific article of Uskha. "Increasing the work capacity of parts of agricultural machines." K., 1971.

Translated by William R. Gill
 Soil Scientist, USDA, ARS, SR
 National Tillage Machinery Laboratory
 P. O. Box 792, Auburn, Alabama 36830
 April 25, 1977

We suggest
consider
established

1. All
not
consider

2. The
of 2

3. The
the
8

4. The
of 2

5. The

6. The
Pop

7. The
on 11
col

8. The
The
The
of 11

9. The
The
The
The
The
The

10. The
The
The
The
The





Fig. 1. Sketch of interactions of a roller with the soil.

Fig. 2. General indicator of the physical-mechanical properties for a soil:
 $W = 20\%$
 $\gamma = 0.4 - 1.4 \text{ g/cm}^3$



$E_0, \text{ kg/cm}^2$




Fig. 3. Modulus of deformation for soil:
 $W = 20\%$
 $\gamma = 0.4 - 1.4 \text{ g/cm}^3$

100

100

(continued)

... ..

1944